



Innovative utility technologies

POWER PUSH



Revolutionary excavator attachment for the safe insertion and feeding of PE pipe and cables

The UIS Power Push completely changes the way pipes and cables are handled throughout the utilities sector.

The Power Push excavator attachment offers a faster, safer and more compliant way of inserting new PE pipe and cable and is fully approved for operation on both live and dead insertions.

The Power Push is easily attached to the excavator arm with minimal operator contact, removing the risk of injuries which may occur during manual projects.

Once attached, the Power Push is fully operated and controlled from the safety of the excavator cab.

The Power Push excavator attachment is compatible for use with the majority of excavators from 1.5T up to 35T and can also be used for slip lining / maneuvering and re-rounding PE pipe of diameters up to 900mm.

AUSTRALIA
03 9068 5688
 +61 3 9068 5688
 sales@blick.group
 www.blick.group

NEW ZEALAND
07 849 2366
 +64 7 849 2366
 sales@blick.group
 www.blick.group





Benefits

- Quick and simple installation and mounting of attachment
- Durable and robust, designed to withstand harsh environments and conditions
- Faster, safer and more convenient way of carrying out live or dead insertion
- Longer sections of pipe can be inserted in one excavation
- Action can be reversed to pull back in case of obstruction, not possible with other insertion methods
- Shim inserts are manufactured and tested for an extensive range of diameters from 50mm – 900mm, giving the best possible gripping and releasing system across the market even in wet conditions
- Simple to operate – no extensive training or special labour required
- Lightweight and compact design for ease of storage and transportation
- Reduces manual handling for a safer, more compliant way of inserting PE pipe
- Instructional videos available outlining all aspects of setup and use of units

Unit Sizes Available

- Up to 180mm
- Up to 300mm
- Up to 400mm
- Up to 630mm
- Up to 900mm
- Bespoke models may be designed to accommodate clients' special requirements

AUSTRALIA

03 9068 5688

+61 3 9068 5688
sales@blick.group
www.blick.group

NEW ZEALAND

07 849 2366

+64 7 849 2366
sales@blick.group
www.blick.group



Unit	Pipe Size Suitability	Excavator Range	Included With Unit
180mm Power Push	Pipe sizes 55mm-180mm	Sizes 1.5T up to 3T	1.5T head bracket, unit storage box, hoses and quick release couplings
300mm Power Push	Pipe sizes 300mm & below	Sizes 3T up to 8T	5T head bracket, 280mm fixed liner, hoses and quick release couplings
400mm Power Push	Pipe sizes 400mm & below	Sizes 5T up to 15T	8T head bracket, 400mm fixed liner, hoses and quick release couplings
630mm Power Push	Pipe sizes 630mm & below	Sizes 8T up to 25T	8T head bracket, 630mm fixed liner, hoses and quick release couplings
900mm Power Push	Pipe sizes 900mm & below	Sizes 15T up to 35T	15T head bracket, 900mm fixed liner, hoses and quick release couplings

Unit	Weight	Height	Length	Width
180mm Power Push (Unit dimensions in storage box)	55kg	420mm	440mm	440mm
180mm Power Push (Shim storage box dimensions (x4 shims inc box))	29kg	370mm	450mm	420mm
300mm Power Push	110kg	650mm	450mm	520mm
400mm Power Push	172kg	700mm	500mm	900mm
630mm Power Push	350kg	1200mm	600mm	900mm
900mm Power Push	680kg	1450mm	600mm	1200mm



AUSTRALIA
03 9068 5688
 +61 3 9068 5688
 sales@blick.group
 www.blick.group

NEW ZEALAND
07 849 2366
 +64 7 849 2366
 sales@blick.group
 www.blick.group

